







TAB1/D-N6

Backbar Cooler

Product Features

- EU Energy Class A
- App. 56% more energy efficient than previous DB-range
- Double glazed tempered glass
- Reversible glass door
- Ventilated cooling for fast pull-down and even temperature
- Easy access electronic thermostat
- · Adjustable shelves
- Adjustable feet
- · LED interior light
- Lock





161 112 84 84

Protective thermostat cover

Adjustable shelves

Energy efficient back bar cooler

This new range of DB back bars is highly energy efficient and uses in average 56% less energy compared to the previous models from the same range. This backbar has ventilated cooling for a short pull-down time to ensure that you can keep up with customer demand for cold beverages. The temperature is easily adjusted on the electronic thermostat.

The back bar cooler has a reversible hinged door with double glazed tempered glass, which gives a nice product presentation. The adjustable wire shelves have a white plastic coating for easy maintenance. The back bar is ideal for busy bar environments, and with its black exterior and stucco aluminium interior it has a contemporary look. A great choice for any bar.

Design and Material	
Door No & Type	1 hinged glass door
Door Reversible	Yes
Tempered glass	Yes
Shelves No & Type	2 wire shelves white
Shelf Color	White
Shelf Dimensions	495x350 mm
Feet / Legs	4 adjustable feet
Exterior Finish	Black
Interior Finish	Stucco aluminium
Interior Light	LED
Lock	Yes

Measures and Content			
Cans 330 ml	pcs	161	
Total Display Area	m²	0,35	
Cans 500 ml	р	112	
Bottles 330 ml	pcs	84	
Bottles 500 ml PET	pcs	84	
Temperature Range	°C	+2 to +10	
Climate Class		4	
Gross / Net Weight	kg	52 / 46	
Gross / Net Volume	I	125 / 115	

Cooling and Functions			
Type of Controller		Electronic	
Type of Cooling		Ventilated	
Type of Defrost		Automatic	
Refrigerant		R600a	
Refrigerant Charge	g	55	
Thermometer		Yes	

Power and Consumption				
Energy Class		Α		
Energy Consumption	kWh/24h	0,96		
Annual Energy Cons.	kWh/year	350		
Power		1		
Max Ambient		30°C at 55% RH		
Input Power	W	95		
Voltage / Frequency	V/Hz	220-240/50		
Noise Level	dB(A)	44		

Dimensions		
Internal Dimension (WxDxH)	mm	510 x 418 x 720
External Dimension (WxDxH)	mm	600 x 520 x 870
Packed Dimension (WxDxH)	mm	685 x 575 x 940
40ft Container Load	pcs	136